



SLG Series 2/2 & 3/2 Solenoid Valve (Normal Close)

How to Order?



SLG

SLG -- -- 22 -- 06 -- E1

SLG Series Blank: NBR
 V: VITON

22: 2/2
23: 3/2

Port Size
06: 1/8"
08: 1/4"

Voltage
E1: AC110V
E2: AC220V
E3: AC380V
E4: DC24V
E5: DC12V
E6: AC38V
E7: AC24V

Order example:

* SLG series, 2 position, 2 port, NBR seal, 1/4" port size, voltage: AC220V, Model: SLG22-08E2

Specifications

Model	SLG22-08E2		SLG23-08E2		SLG23-08E2	
	* With Voltage AC220V					
Working Medium	Air, Water, Oil					
Orifice(mm)	1.6					
Cv Value	0.1					
Port Size	1/8"	1/4"	1/8"	1/8"	1/4"	1/4"
Working Pressure(Bar)	0-16		0-9			
Voltage Range	±10%					
Seal Material	NBR or VITON					



EMCF Series 2/2 Pulse Valve (Normal Close)

How to Order?



EMCF-25

EMCF-50

EMCF -- 25 -- E1

EMCF Series

Orifice
25: 25mm
40: 40mm
50: 50mm
65: 65mm
76: 76mm

Voltage
E1: AC110V
E2: AC220V
E4: DC24V

Order example:

* EMCF series, Orifice: 25mm, Voltage: AC220V, Model: EMCF-25E2

Specifications

Model	* With Voltage AC220V				
	EMCF-25E2	EMCF-40E2	EMCF-50E2	EMCF-65E2	EMCF-76E2
Working Pressure(Bar)	4-6				
Working Temperature(°C)	-10-55				
Relative Humidity	<85%				
Working Medium	clean air				
Voltage	AC220V/DC24V				
Diaphragm Life	over one 1,000,000 cycles				
Orifice	φ25	φ40	φ50	φ65	φ76
Port Size	1"	1-1/2"	2"	2-1/2"	3"

EQ Series 2/2 Solenoid Valve (Normal Close)

How to Order?

EQ -- 20 -- 25

EQ Series

Orifice
20: 22mm
50: 50mm

Port Size
25: 1"
50: 2"



EQ

Order example:

* EQ series, 2 position, 2 port, Orifice: 22mm, 1" port size, Model: EQ20-25

Specifications

Model	EQ20-25		EQ50-50	
	Orifice(mm)	22	50	50
Cv Value	12	48	48	48
Port Size	1"	2"	2"	2"
Fluid Viscosity	50 CST Below			
Working Pressure(Bar)	0-7			
Max. Pressure Resistance(Bar)	11			
Control Pressure Range (Bar)	3-8			
Working Temperature Range(°C)	-5-100			
Material of Valve Body	Brass			
Seal Material	PTFE			
Control Port Size	2-G1/8"		2-G1/4"	

EMCYF Series 2/2 Pulse Valve (Normal Close)

How to Order?

EMCYF -- 50 -- E1

EMCYF Series

Orifice
50: 50mm
62: 62mm
76: 76mm

Voltage
E1: AC110V
E2: AC220V
E4: DC24V



EMCYF-50

Order example:

* EMCYF series, Orifice: 50mm, Voltage: AC220V, Model: EMCYF-50E2

Specifications

Model	* With Voltage AC220V		
	EMCYF-50E2	EMCYF-62E2	EMCYF-76E2
Working Pressure(Bar)	2-6		
Working Temperature(°C)	-10-55		
Relative Humidity	<85%		
Working Medium	clean air		
Voltage	AV220V/DC24V		
Diaphragm Life	over one million cycles		
Orifice	φ50	φ62	φ76
Port Size	φ65	φ80	φ99