ESV 3/2 Direct Acting Solenoid Valve (Normal Close)

New

ESV1-06E2-1.5L

ESV1-06E2-1.5LS2

How to Order?

ESV -- 1 - 06 -- E1 -- [ ] -- [ ] - 1.5L -- [ ]

- ESV 3/2 Series
- Control style: 1: Normal Close; 2: Normal Open; 3: Universal
- Port Size: 06:1/8"; 08:1/4"
- Voltage: E1: AC110V; E2: AC220V; E4: DC24V; E5: DC12V; E7: AC24V
- Coil Type: Blank: DIN Type; F: Flying Leads
- Seal Material: Blank: NBR; V: VITON; E: EPDM
- Orifice Φ mm: 1.5L: 1.5; 2L: 2.0; 3L: 3.0; 4L: 4.0; 5L: 5.0
- Valve body Material: Blank: Brass; S2: SS304

Order example:

* ESV series, 2 position, 3 port, normal close,AC110V, 1/8" port size,orifice 1.5mm,brass valve body,NBR seal,Model: ESV1-06E1-1.5L
* ESV series, 2 position, 3 port, normal open,AC220V, 1/4" port size,orifice 3mm,stainless steel valve body,VITON seal,Model: ESV2-08E2-V3LS2



OFF



ON

Joint Size	Orifice (mm)	CV Value	Pressure Difference (Bar) Min. Pressure	Max. Working Pressure: Air、Gas、Water、Hot Water、Liquid AC	Max. Working Pressure: Air、Gas、Water、Hot Water、Liquid DC	Light Oil ≤20CST AC	Light Oil ≤20CST DC	Max. Temperature (℃)	Power VA: AC 220V	Power W: DC 24V	Model 220VAC 50/60Hz: Brass	Model 220VAC 50/60Hz: SS304
1/8"	1.5	0.07	0	13	11	13	11	80	22	13	ESV1-06E2-1.5L	ESV1-06E2-1.5LS2
	1.5	0.07	0	13	11	13	11	120	22	13	ESV1-06VE2-1.5L	ESV1-06VE2-1.5LS2
	2.0	0.14	0	11	9	11	9	80	22	13	ESV1-06E2-2.0L	ESV1-06E2-2.0LS2
	2.0	0.14	0	11	9	11	9	120	22	13	ESV1-06VE2-2.0L	ESV1-06VE2-2.0LS2
	2.5	0.21	0	9	7	9	7	80	22	13	ESV1-06E2-2.5L	ESV1-06E2-2.5LS2
	2.5	0.21	0	9	7	9	7	120	22	13	ESV1-06VE2-2.5L	ESV1-06VE2-2.5LS2
	3.0	0.25	0	6	4	6	4	80	22	13	ESV1-06E2-3.0L	ESV1-06E2-3.0LS2
	3.0	0.25	0	6	4	6	4	120	22	13	ESV1-06VE2-3.0L	ESV1-06VE2-3.0LS2
1/4"	1.5	0.07	0	13	11	13	11	80	22	13	ESV1-08E2-1.5L	ESV1-08E2-1.5LS2
	1.5	0.07	0	13	11	13	11	120	22	13	ESV1-08VE2-1.5L	ESV1-08VE2-1.5LS2
	2.0	0.14	0	11	9	11	9	80	22	13	ESV1-08E2-2.0L	ESV1-08E2-2.0LS2
	2.0	0.14	0	11	9	11	9	120	22	13	ESV1-08VE2-2.0L	ESV1-08VE2-2.0LS2
	2.5	0.21	0	9	7	9	7	80	22	13	ESV1-08E2-2.5L	ESV1-08E2-2.5LS2
	2.5	0.21	0	9	7	9	7	120	22	13	ESV1-08VE2-2.5L	ESV1-08VE2-2.5LS2
	3.0	0.25	0	6	4	6	4	80	22	13	ESV1-08E2-3.0L	ESV1-08E2-3.0LS2
	3.0	0.25	0	6	4	6	4	120	22	13	ESV1-08VE2-3.0L	ESV1-08VE2-3.0LS2



OFF



ON

Joint Size	Orifice (mm)	CV Value	Pressure Difference (Bar) Min. Pressure	Max. Working Pressure: Air、Gas Water、Hot Water、Liquid AC	Max. Working Pressure: Air、Gas Water、Hot Water、Liquid DC	Light Oil ≤20CST AC	Light Oil ≤20CST DC	Max. Temperature (℃)	Power VA: AC 220V	Power W: DC 24V	Model 220VAC 50/60Hz: Brass	Model 220VAC 50/60Hz: SS304
1/8"	1.5	0.07	0	7	5	7	5	80	22	13	ESV3-06E2-1.5L	ESV3-06E2-1.5LS2
	1.5	0.07	0	7	5	7	5	120	22	13	ESV3-06VE2-1.5L	ESV3-06VE2-1.5LS2
	2.0	0.14	0	5	4	5	4	80	22	13	ESV3-06E2-2.0L	ESV3-06E2-2.0LS2
	2.0	0.14	0	5	4	5	4	120	22	13	ESV3-06VE2-2.0L	ESV3-06VE2-2.0LS2
1/4"	1.5	0.07	0	7	5	7	5	80	22	13	ESV3-08E2-1.5L	ESV3-08E2-1.5LS2
	1.5	0.07	0	7	5	7	5	120	22	13	ESV3-08VE2-1.5L	ESV3-08VE2-1.5LS2
	2.0	0.14	0	5	4	5	4	80	22	13	ESV3-08E2-2.0L	ESV3-08E2-2.0LS2
	2.0	0.14	0	5	4	5	4	120	22	13	ESV3-08VE2-2.0L	ESV3-08VE2-2.0LS2



OFF



ON

Joint Size	Orifice (mm)	CV Value	Pressure Difference (Bar) Min. Pressure	Max. Working Pressure: Air、Gas,Water、Hot Water,Liquid AC	Max. Working Pressure: Air、Gas,Water、Hot Water,Liquid DC	Light Oil ≤20CST AC	Light Oil ≤20CST DC	Max. Temperature (℃)	Power VA: AC 220V	Power W: DC 24V	Model 220VAC 50/60Hz: Brass	Model 220VAC 50/60Hz: SS304
1/8"	1.5	0.07	0	13	11	13	11	80	22	13	ESV2-06E2-1.5L	ESV2-06E2-1.5LS2
	1.5	0.07	0	13	11	13	11	120	22	13	ESV2-06VE2-1.5L	ESV2-06VE2-1.5LS2
	2.0	0.14	0	11	9	11	9	80	22	13	ESV2-06E2-2.0L	ESV2-06E2-2.0LS2
	2.0	0.14	0	11	9	11	9	120	22	13	ESV2-06VE2-2.0L	ESV2-06VE2-2.0LS2
	2.5	0.21	0	9	7	9	7	80	22	13	ESV2-06E2-2.5L	ESV2-06E2-2.5LS2
	2.5	0.21	0	9	7	9	7	120	22	13	ESV2-06VE2-2.5L	ESV2-06VE2-2.5LS2
	3.0	0.25	0	6	4	6	4	80	22	13	ESV2-06E2-3.0L	ESV2-06E2-3.0LS2
	3.0	0.25	0	6	4	6	4	120	22	13	ESV2-06VE2-3.0L	ESV2-06VE2-3.0LS2
1/4"	1.5	0.07	0	13	11	13	11	80	22	13	ESV2-08E2-1.5L	ESV2-08E2-1.5LS2
	1.5	0.07	0	13	11	13	11	120	22	13	ESV2-08VE2-1.5L	ESV2-08VE2-1.5LS2
	2.0	0.14	0	11	9	11	9	80	22	13	ESV2-08E2-2.0L	ESV2-08E2-2.0LS2
	2.0	0.14	0	11	9	11	9	120	22	13	ESV2-08VE2-2.0L	ESV2-08VE2-2.0LS2
	2.5	0.21	0	9	7	9	7	80	22	13	ESV2-08E2-2.5L	ESV2-08E2-2.5LS2
	2.5	0.21	0	9	7	9	7	120	22	13	ESV2-08VE2-2.5L	ESV2-08VE2-2.5LS2
	3.0	0.25	0	6	4	6	4	80	22	13	ESV2-08E2-3.0L	ESV2-08E2-3.0LS2
	3.0	0.25	0	6	4	6	4	120	22	13	ESV2-08VE2-3.0L	ESV2-08VE2-3.0LS2

EWSLC Series 2/2 Direct Acting Solenoid Valve (Normal Close)

For Drinking Fountain

EWSLC1

EWSLC2

How to Order?

EWSLC -- 1 -- E1

- EWSLC Series
- 1: 1/8" Port Size 2.5mm Orifice; 2: 1/4" Port Size 2.5mm Orifice
- Voltage: E1:AC110V; E2: AC220V; E4: DC24V; E7: AC24V

Order example:

* EWSLC1 Series, 1/8" Port Size, Orifice: 2.5mm,AC220V,Model: EWSLC1E2

Specifications

Model	EWSLC1E2	EWSLC2E2
Working Medium	Water	
Acting Type	Direct Acting	
Type	2/2 Normal Close	
Orifice	2.5(3/32)	
Cv Value	0.21	
Port Size	1/8"	1/4"
Working Pressure(Bar)	0-8	
Temperature(℃)	0-80	
Medium Temperature(℃)	-10~40	
Seal Material	EPDM	
Valve Body	PP 1/8(Black) 1/4(White) Nylon66	